



OP-117 Specifications

LCD Display	17" TFT Active Matrix Panel
Display Size	337.92 x 270.34 mm
Pixel Pitch	0.264 x 0.264 mm
Display Mode	VGA 640x350 (70Hz) VGA 720x400 (70Hz) VGA 640x480 (60/72/75Hz) SVGA 800x600 (60/72/75Hz) XGA 1024x768 (60/70/75Hz) SXGA 1280x1024 (60/70/75Hz) Mac. 832x624 (75Hz)
Max. Resolution	1280x1024
Contrast Ratio	500:1
Brightness	250 cd/m²
Response Time	15mS (Rising), 10mS (Falling)
Display Colors	16M (dithering)
Viewing Angle	+85⁰ ~ -85⁰(L/R), +85⁰ ~ -85⁰(U/D)
Input Signal	
Video	R.G.B Analog 0.7V Peak-to-Peak
Sync	TTL Positive or Negative
Signal Connector	15Pin Mini D-sub
Front Control	Power Switch, Menu, Select (Up, Down), Adjust (+, -)
OSD	Auto-Adjustment, Contrast, Brightness, Clock, Phase, H-Position, V-Position, Color Temperature, Load default
Plug & Play	DDC1/2B
Optional	Touch Screen Video in: Pal/NTSC & S-video/AV connector Audio System: 1W per channel
Power	Universal 90-240V, 12V/45W
Dimensions	430 x 360 x 55 mm
Weight (Net)	7 Kg
Certification	FCC-B, CE, UL

